



HIGH PERFORMANCE INORGANIC SELF SET AND GAS SET BINDERS

INORGANIC BINDERS

PRODUCT RANGE FOR FERROUS AND NON FERROUS FOUNDRIES

No odour and emissions

Easily reclaimable

Good break down

Improved mixed sand flowability

Superior strength



Inorganic binders

Product range for ferrous and non ferrous foundries

Driven by increasing health and safety guidelines and even more stringent environmental legislation, the sodium silicate method in combination with CO₂ gas or liquid hardeners has enjoyed a recent resurgence in popularity in steel, iron and non ferrous foundries. This is due to the fact that harmful emissions associated with the use of organic binding agents can be largely, and in some cases completely, avoided. The production of moulds and cores using liquid hardeners or CO₂ gas can also be described as odour-free, meaning that silicate binders can be classified as environmentally friendly binding agents. In combination with modern reclamation systems, reclaim rates can now be achieved that were only possible with organic binders.

AMASILIC & CARSIL

These systems fulfill highest demands on reclamation, mixed sand bench-life and final strength properties.

Benefits

- Applicable with standard equipment
- High reactivity
- High strength
- Low viscosity
- High reclaim rates

SOLOSIL*, NUCLEPON & AMASILIC GS

These products fulfill different demands on strength, break down and mixed sand flowability requirements.

Benefits

- Standard core manufacturing equipment applicable
- High strength
- Low viscosity
- Good mixed sand flowability

Brand	Application	Properties
SOLOSIL	CO ₂ gas set for core making	These systems offer a variety of strength, breakdown and mixed sand flowability characteristics
AMASILIC GS		
NUCLEPON		
CARSIL	Catalysed self setting for mould making	These systems fulfill the highest demands on reclamation, mixed sand bench-life and final strength properties
AMASILIC		

Odour and emission free working environment



Compatible with existing mixing equipments



Excellent casting finish

*FOSECO, the Logo and SOLOSIL are trade marks of the Vesuvius Group, registered in certain countries, used under licence. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system of any nature or transmitted in any form or by any means, including photocopying and recording, without the written permission of the copyright holder or as expressly permitted by law. Applications for permission shall be made to the publisher at the address mentioned.

Warning: The doing of an unauthorised act in relation to a copyright work may result in both a civil claim for damages and criminal prosecution. All statement, information and data contained herein are published as a guide and although believed to be accurate and reliable (having regard to the manufacturer's practical experience) neither the manufacturer, licensor, seller nor publisher represents nor warrants, expressly or impliedly: (1) their accuracy/reliability, (2) that the use of the product(s) will not infringe third party rights, (3) that no further safety measures are required to meet local legislation. The seller is not authorised to make representations nor contract on behalf of the manufacturer/licensor. All sales by the manufacturer/seller are based on their respective conditions of sale available on request.

© Foseco International Limited 05/11.

Foseco International Limited
 Drayton Manor Business Park,
 Tamworth, Staffordshire,
 England B78 3TL
 Phone: +44 (0)1827 262021
 Fax: +44 (0)1827 283725
 www.foseco.com

Please contact your local Foseco team

VESUVIUS



COMMITTED TO FOUNDRIES